

ACCESSORIES

FOR AUTOMATIC LUBRICATOR



ACCESSORIES

- Progressive Distribution Blocks and Kits - 2,3,4,6,8,12 Port
- Battery Packs – Alkaline + Lithium
- Brackets / Clamps
- Adaptors – Standard & Metric
- Mounting Plates
- Weatherproof Caps (Optional)
- Nylon Hose
- Oil Brush
- Remote Control Options
 - Remote Control
 - Remote Power
 - Remote Power + Remote Control
 - DC Power
 - DC Power + Remote Control
 - Vibration Sensor Control
 - Motion Activated Control
 - Pulse Counter Control
- Bluetooth in Progress



ABOUT US

A.T.S. ELECTRO-LUBE™ INTERNATIONAL INC. has been manufacturing and selling ELECTRO-LUBE™ Automatic Electronic Lube Dispensers worldwide for 40 years. The product was invented and designed by our founder, and is manufactured in British Columbia, Canada.

With market trends changing, the company introduced a new line of motorized lubricators for the industrial market. The ULTIMATE LUBER™ series provides single and multi-point lubrication using progressive distribution blocks. These units are the most powerful self-contained lubricators in the world.

The TITAN CL LUBER™ was then introduced, which incorporates the proven pump and electronics of our ULTIMATE series while using industry standard grease cartridges for ease of refilling. The dual cartridge TITAN II motor-driven lubricant dispenser followed.

The latest additions to our product line of lubricators are the powerful TITAN OILER and the JACK-LUBER™. We also offer a variety of accessories to complement our products.

ATS is committed to improving and developing products to satisfy the growing needs of industries for decades to come. We will continue to adapt to market demands and expand our product line with the same dedication to quality as we always have. You can depend on ATS to sell only top-of-the-line, versatile, automatic lubrication equipment for your every application.



40 YEARS OF MANUFACTURING RELIABLE LUBRICATION PRODUCTS FOR AN INDUSTRIAL WORLD

TYPICAL INDUSTRIES AND APPLICATIONS

Mining/Minerals	Stacker Cranes Crushers/Grinders/Shakers Bucket Elevators Conveyors Slurry Pumps
Manufacturing	Bridge Cranes Conveyors Hoists Heat Treat furnaces Chain Lubricators Robots
Oil and Gas	Electric Motor Pump Jacks Cooling Fans
Energy	Coal Handling Equipment Drills, Pumps Refinery Operations Wind Turbines
Food and Beverage	Packaging Lines Mixers Washers, Dryers Can/Bottling Lines Ovens
Building Maintenance	Elevators/Escalators Motors HVAC Air Handlers/Filters
Municipal	Waste Water Treatment Potable Water Plants Incinerators
Metals	Rolling Mills Material Handling Cooling Pumps
Pulp and Paper	Furnace Trunions and Fans Lumber Mills Paper and Fiberboard Mfg. Slurry Pumps
Agriculture	Dryers Flour Mills Grain Mills Feed Mills

THE MOST
POWERFUL
SELF-CONTAINED
LUBRICATORS
IN THE WORLD



 **ATS ELECTRO-LUBE**
INTERNATIONAL INCORPORATED



ELECTRO-LUBER SERIES

GAS-DRIVEN LUBRICANT DISPENSER – 50 PSI

JACK SERIES

MOTOR-DRIVEN JACKSCREW LUBRICANT DISPENSER – 200 PSI

ULTIMATE SERIES

MOTOR-DRIVEN LUBRICANT DISPENSER – 1000 PSI

TITAN SERIES

MOTOR-DRIVEN LUBRICANT DISPENSER – 1000 PSI

Remote Control Options available for all series



16 oz/
475cc 8 oz/
250cc 4 oz/
125cc 2 oz/
60cc



Jack 125 Luber &
Replacement Cartridge



Jack 250 Luber &
Replacement Cartridge







17 oz/
500cc 8 oz/
250cc 4 oz/
125cc 2 oz/
60cc

Includes Internal
Homogenizing Mixer



Titan II Titan Titan Oiler

Includes Internal
Homogenizing Mixer

COMPARE AT A GLANCE	ELECTRO-LUBER SERIES		JACK SERIES		ULTIMATE SERIES		TITAN SERIES	
APPLICATION	Single Point		Single Point		Single and Multi-point (up to 12 points)		Single and Multi-point (up to 12 points)	
SIZES	Available in 2, 4, 8, or 16 oz. capacity (60, 125, 250 or 475cc)		Available in 4 oz. capacity (125cc) & 8 oz. (250cc) capacity		Available in 2, 4, 8, or 17 oz. capacity (60, 125, 250 or 500cc)		Requires 1 or 2 - 14oz. grease cartridge. Oiler has 47 oz. capacity	
TECHNOLOGY	Safe, Inert Nitrogen gas powered		Jackscrew mechanism		Powerful mechanical fixed-displacement pump		Powerful mechanical fixed-displacement pump. Proven Ultimate Series technology	
DISPENSING POWER	Up to 50 psi/3.45 bar. Single Point can be remote mounted to 3 ft. using 1/4" ID hose		200 psi/13.79 bar. Single Point can be remote mounted up to 20ft using 1/4" ID hose.		Over 1000 psi/68.95 bar. Single Point can be remote mounted up to 35 ft. Multi-Point can be remote mounted up to 20ft using 1/4" ID hose. Distribution blocks available.		Over 1000 psi/68.95 bar. Single Point can be remote mounted up to 35 ft. Multi-Point can be remote mounted up to 20 ft. Oiler up to 200 ft. or multi-point up to 60ft using 1/4" ID hose. Distribution blocks available.	
POWER SOURCE	AA Alkaline Batteries		Lithium Battery pack or remote AC/DC power		Alkaline Battery pack or remote AC/DC power Optional lithium battery pack - 4 or 8 cells		Alkaline Battery pack or remote AC/DC power Optional lithium battery pack - 8 cells	
CYCLE	Single use, Disposable		Reusable motor drive unit and easily replaceable single-use cartridge		Refillable with standard grease gun or pump		Refillable with standard grease cartridge(s). Oiler refillable through screened port	
LUBE CHOICE	Customer specified lube		Customer specified lube. Replaceable cartridge		Customer Fill/Refill as needed		Customer replaced cartridge or oiler refilled as needed	
OPERATING SPAN	15 days to 1 year on factory filled unit		Variable from 15 days to 2 years. Optional custom programming available		Variable from 15 days to 2 years. Optional custom programming available		Variable from 15 days to 2 years. Optional custom programming available	
LED INDICATORS	Red LED - Positive verification unit is working		Tri-color LEDs indicate normal operation, low battery		Tri-color LEDs to indicate normal operation, low battery, low temp.		Tri-color LEDs indicate normal operation, low battery, low lube level, low temp. Oiler has low lube indicator.	
WEATHERPROOF	Waterproof (Submerged) to 30 ft Temp range -40°F to 131°F (-40°C to 55°C) Weathercap available upon request		Suitable for outdoor use in temp range -4°F to 131°F (-20°C to 55°C). Use special lithium battery pack for colder/hotter temperatures. Weathercap included + must be used.		Suitable for outdoor use in temp range -4°F to 131°F (-20°C to 55°C) Weathercap included + must be used		Suitable for outdoor use in temp range -4°F to 131°F (-20°C to 55°C) Weathercap included for cartridge and motor housing.	
DISPENSING RATE	Established constant flowrates, simply select and install		Standard timed intervals or custom programming available		Standard timed intervals or custom programming available		Standard timed intervals or custom programming available	
APPROVALS	UL & CUL approved Intrinsically Safe for all areas; Class I, Groups A, B, C, D; Class II, Groups E, F, G; Class III, hazardous locations; MSHA; ATEX and IECEx 		Class I, Div 2, Groups A, B, C, D. Class II, Div 2, Groups F & G Class III hazardous locations  T-Code T6 55°C PATENTED		Class I, Div 2, Groups A, B, C, D. Class II, Div 2, Groups F & G Class III hazardous locations  T-Code T6 55°C PATENTED		Class I, Div 2, Groups A, B, C, D. Class II, Div 2, Groups F & G Class III hazardous locations  T-Code T6 55°C PATENTED	