


T3-D & T3-M SERIES

A Clean Oil Supply You Can Wheel Anywhere.

The T3 is a 30-gallon tank, a filter and a pump on four wheels. It fills itself, filters oil already in a reservoir, and dispenses into whatever needs topping up, so one unit covers the whole job.

30

GALLON STEEL TANK

1-10

GPM FLOW RATES

600

CST MAX VISCOSITY

150

PSI PUMP RELIEF

16

MODELS IN THE RANGE

Two Series, One Tank

Both series use the same 30-gallon tank, four-wheel frame, pump and motor options. They differ in the filter heads, the change-out indicator, the standard element and weight.

T3-D Series
MEDIUM PRESSURE HEADS

Filter heads **Cast aluminium**

Standard elements **Water removal + 7 micron**

Indicators **Slide bar**

Weight **Approx. 150 lb**

Models **8**
T3-M Series
FINER STANDARD ELEMENT

Filter heads **Aluminium**

Standard elements **Water removal + 3 micron**

Indicators **Pop-up @ 50 psid**

Weight **Approx. 125 lb**

Models **8**

Where It Is Used

TYPICAL APPLICATIONS

- Filtering contaminated systems
- Flushing new or repaired systems
- Pre-filtering new oil
- Transferring oil
- Topping off reservoirs or containers
- Dispensing new oil

STANDARD ON EVERY MODEL

- 30 gallon carbon steel tank
- Desiccant breather
- Two elements incl. water removal
- Internal pump bypass
- 7 ft suction & return hoses
- ISO-B quick disconnects

Full Specification

Specification	T3-D Electric	T3-D Air Operated	T3-M Electric	T3-M Air Operated
Flow rates	1 / 2 / 5 / 10 GPM	1 / 2 / 5 / 10 GPM	1 / 2 / 5 / 10 GPM	1 / 2 / 5 / 10 GPM
Tank	30 gal carbon steel	30 gal carbon steel	30 gal carbon steel	30 gal carbon steel
Motor	1 HP electric	1.5 HP air operated	1 HP electric	1.5 HP air operated
Air preparation	-	Filter, regulator, lubricator	-	Filter, regulator, lubricator
Pump / relief	Cast steel gear @ 150 PSI	Cast steel gear @ 150 PSI	Cast steel gear @ 150 PSI	Cast steel gear @ 150 PSI
Filter heads	Cast aluminium, medium pressure	Cast aluminium, medium pressure	Aluminium	Aluminium
Standard elements	Water removal + 7 micron	Water removal + 7 micron	Water removal + 3 micron	Water removal + 3 micron
Filter indicators	Slide bar (electric optional)	Slide bar (electric optional)	Pop-up @ 50 psid	Pop-up @ 50 psid
Desiccant breather	Yes	Yes	Yes	Yes
Cord	40 ft retractable reel	Runs on shop air	40 ft retractable reel	Runs on shop air
Frame	Carbon steel, 4 wheels	Carbon steel, 4 wheels	Carbon steel, 4 wheels	Carbon steel, 4 wheels
Dimensions	30" L x 19" W x 35" H	30" L x 19" W x 35" H	30" L x 19" W x 35" H	30" L x 19" W x 35" H
Weight (approx.)	150 lb	150 lb	125 lb	125 lb
Max viscosity	600 cSt (ISO VG 680)	600 cSt (ISO VG 680)	600 cSt (ISO VG 680)	600 cSt (ISO VG 680)

Hose and quick-disconnect sizes follow the flow rate: 3/4" suction and 1/2" return on 1, 2 and 5 GPM totes; 1" suction and 3/4" return on 10 GPM totes. Replacement elements are series specific and are NOT interchangeable: the D element is 5" x 14" on a 1 3/4"-12 thread rated to 350 PSI, the M element 5.06" x 10.86" on a 1 1/2"-16UN thread rated to 175 PSI. D-Series: P1066 (4 micron, Beta 4 = 2000), P1065 (7 micron, Beta 7 = 2000), P1063 (10 micron, Beta 10 = 1000), P1064 (25 micron, Beta 25 = 2000), P1048WR (water removal). M-Series: P1068 (3 micron, Beta 3 = 1000), P1069 (6 micron, Beta 6 = 1000), P1070 (10 micron, Beta 10 = 1000), P1071 (25 micron, Beta 25 = 1000), P1072WR (water removal). Outside Canada the D water-removal element is P1048WR-USA.

Available Models

Every T3 filter tote in the range, by series and drive. Custom builds carry an -S suffix and are quoted individually.

T3-D Series — 8 models

Drive	1 GPM	2 GPM	5 GPM	10 GPM
Electric	T3D1SHSQ	T3D2SHSQ	T3D5SHSQ	T3D10SHSQI
Air Operated	T3D1MSHSQ	T3D2MSHSQ	T3D5MSHSQ	T3D10MSHSQI

T3-M Series — 8 models

Drive	1 GPM	2 GPM	5 GPM	10 GPM
Electric	T3M1SHSQ	T3M2SHSQ	T3M5SHSQ	T3M10SHSQI
Air Operated	T3M1MSHSQ	T3M2MSHSQ	T3M5MSHSQ	T3M10MSHSQI